

GALVEX SPRAY



PRODUCT DESCRIPTION:

GALVEX spray is a galvanic action, anti-corrosion special paint with a very high (80 -90%) content of microfine metallic zinc dust in a synthetic binder.

APPLICATION:

GALVEX spray is extremely suitable for the repair of damaged surfaces on hot-galvanized items as well as for corrosion protection of welding seams and cutting places. Also very suitable for preliminary treatment of all surfaces where EXTRA HIGH PROTECTION against rust is required.

TECHNICAL PROPERTIES:

GALVEX spray, which is ready for use after a quick shaking, provides a nice mat-grey colour. GALVEX spray provides effective and long-acting protecting against corrosion and prevents rust from spreading from non-protected areas. Welding on GALVEX protected iron is possible. GALVEX protects materials from fungus attack in eventual finish coating applications. Withstands constant heat effects following hardening (3-5 days) up to 110°-120°C. May be overcoated after 1 – 3 days. Handling dry after 5 – 15 min.

DIRECTIONS:

To achieve the possible contact between zinc particles and iron the surface has to be cleaned thoroughly for oil, dirt, loose rust and paint. An ideal preliminary treatment is sand blasting. Shake GALVEX spray before use and at regular intervals while using it. Keep the spray straight-up-and-down and about 25cm from the item. The application is done with regular motions from side to side. Slip the nozzle between the motions to prevent the paint from "running". The best result is achieved at spraying "in all directions". Clean the nozzle after use at turning the spray upside down and spraying for a moment until zinc colour no longer appears. 2 coats of paint are recommended if only GALVEX is used. Second coating after 15-20 min. Finish with aluminium spray, if necessary, to adjust the colour to hot-galvanized items.

The data contained here are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein.

Does not contain ozon hazardous freon.

SAFETY CODE FOR PAINTING: 4 - 1
Contains xylen.

PACKAGING:		Item no.	VVS-no.	RSK-no.	NRF-no.	LVI- no.
500 ml. aerosol spray	12 pcs./box	2500000	271802005	4054180	9507785	3188326

Please see **SAFETY DATA SHEET**

As we constantly develop our products and we reserve the right to make changes without prior notice.