

Safety Data Sheet

In accordance with REACH Regulation (EC) no. 1907/2006

1. Identification of the substance/mixture and of the company/undertaking.

Product name: GALVEX THINNER

Use: Thinning of brush-applied paint

Product registration no.: -

Date: 12.12.1994

Revised on: 11.03.2010

Contact person: lja@eurofins.dk

Phone no. for emergencies: +45 86 26 11 77

+45 82 12 12 12 (Bispebjerg Hospital, Giftlinje ("Toxins Line"))



2. Hazards identification

The product has hazard classification Xn, N; R10-37-51/53-65-66-67.

The product contains a solvent which on inhalation in large quantities over a prolonged period may damage the central nervous system.

The product is flammable. The product is harmful to the environment.

3. Composition/information on ingredients

Selected ingredients	EINECS/ ELINCS	CAS no.	Wt-%	Classification
Solvent naphtha (petroleum) light aromatic	265-199-0	64742-95-6	100	F;R10 Xn;R65 Xi;R37 N;R51/53 R66 R67 ClaP*: Flam Liq. 3: H226 Asp. Tox. 1: H304 STOT SE 3: H335 STOT SE 3: H336 Aquatic Chronic 2: H411 EUH066

ClaP*: European Parliament and Council Regulation (EC) no. 1272/2008. 1272/2008.
The full text of R and H phrases is given in Par. 16.

4. First-aid measures

Inhalation:

Remove casualty to fresh air. If there is no immediate improvement, seek medical advice.

Skin contact:

Wash the skin with plenty of soap and water. After washing, rub skin with a thick cream. If the irritation does not stop immediately, seek medical advice.

Eye contact:

Open the eye wide and rinse with plenty of water for at least 15 minutes. If the irritation does not improve, seek medical advice.

Swallowing:

Do not provoke vomiting. Give the casualty water or milk to drink. Seek medical advice immediately.

Burns:

Flush with water until the pain stops. During flushing, remove clothing which is not burnt onto the skin from the burnt area. If medical treatment is necessary, continue flushing until the doctor takes over treatment.

5. Fire-fighting measures

The product is flammable.

As far as possible remove the product from areas threatened by fire. Use supplied-air respirator for fire fighting. Toxic gases (e.g. carbon monoxide) are emitted in the case of fire.

Extinguish the fire with carbon dioxide, foam, powder or water mist.

6. Accidental release measures

Avoid ignition sources. No smoking.
In case of release to the external environment, contact the environmental authorities.
Cover/absorb large quantities of released material with sand or other absorbent material.
These must then be treated as waste. See also Pars. 8 and 13.
Do not let the product run into drainage systems.

7. Handling and storage

Ensure there is good ventilation when using the product. If this is not possible approved breathing masks must be worn. See Par. 8.
Avoid contact with skin and eyes. Use protective gloves. Where there is a risk of splashing, protective goggles should be worn. See Par. 8.
Store the product in the closely sealed original packaging in a cool and well-ventilated place.
Fire hazard class: II-1, One storage unit: 5 litres.

8. Exposure controls/personal protection

The following notifiable ingredients have a threshold value under Danish Working Environment Authority Instruction (At-anvisning) C.0.1, 2007:

Petroleum (solvent naphtha) 25 ppm (Advisory)

Compliance with threshold value can be checked with occupational hygiene measurements.

In the case of a workplace user instruction, it must be ensured that employees are not exposed to effects which could present a risk for pregnancy or breast-feeding.

The following personal protective measures are recommended, where necessary:

Breathing apparatus:	Gloves:	Eye protection:
Rubber half-mask/A2 filters	4H or similar quality	Goggles if necessary.

9. Physical and chemical properties

Appearance:	Liquid	Solubility in water:	-
	-	Partition coefficient	
Odour:	-	n-octanol/water:	-
pH:	-	Flash point:	47°C
Boiling point:	-	Self-ignition temperature:	-
Melting point:	-	Explosion limits:	0.5-8 vol%
Vapour pressure (20°C):	0.87 kg/l	Viscosity:	-
Density:			

-: Means no data or not applicable

10. Stability and reactivity

On contact with strong oxidants, heating and formation of flammable vapours may occur.
On heating, vapours are emitted which may ignite and form explosive mixtures with air.

11. Toxicological information

Inhalation:

Vapour from the product has a highly irritant effect on the respiratory system and can lead to drowsiness, dizziness, headache and general feelings of unwellness.

Skin contact:

The product has an irritant effect on contact with the skin. Repeated exposure may result in dry or cracked skin.

Eye contact:

The product has an irritant effect on contact with the eyes.

Swallowing:

Swallowing will cause nausea, discomfort and possible vomiting. May cause lung damage if swallowed.

Long-term effects:

Repeated or prolonged exposure to the product may damage the central nervous system.

12. Ecological information

Danger to aquatic environments: Solvent naphtha (petroleum) is classified as toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment according to Danish Environment Ministry rules. With regard to other ingredients there is insufficient data for an environmental classification according to Danish Environment Ministry rules.

The product must be classified as toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment according to Danish Environment Ministry rules.

Danger to other ecosystems: Insufficient data.

13. Disposal considerations

Waste catalogue code (EAK Code): 08 03 12. The product is regarded as hazardous waste. Spillage and residues to be disposed according to Local Authority instructions e.g. a municipal receiving station for chemical waste.

In case of disposal to Kommunekemi, please quote chemical wastes group: H.

For transport as waste: See Par. 14.

14. Transport information

UN No.: 1268; **ADR/RID class:** 3; **Classification code:** F1; **Packaging group:** III;
Goods description: Petroleum distillates; **IATA:** 3; **IMDG:** 3; **EmS:** F-E, S-E

15. Regulatory information

Hazard label on packaging:

Contains: Solvent naphtha (petroleum) light, aromatic

Flammable (R10)

Irritating to respiratory system (R37)

Toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment (R51/53)

Harmful: may cause lung damage if swallowed (R65)

Repeated exposure may cause skin dryness or cracking (R66)

Vapours may cause drowsiness or dizziness (R67)

Do not breathe vapour (S23)

Avoid contact with skin (R24)

Avoid release to the environment. Refer to special instructions/safety data sheet (S61)

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label (S62)



MAL code (1993): 5-1

Limitations on use: May not be used by young people under 18 years (except apprentices).

Requirements for special training: None.

Also covered by the following special statutory instruments:

- Statutory Instrument on work with coded products, no. 302 of 13 May 1993

Requirement for workplace user instruction as the product contains $\geq 1\%$ of a substance classified as hazardous to health under Danish Environment Ministry rules.

16. Other information

The following paragraphs have been revised: 1, 2, 3, 4, 6, 7, 8, 10, 11, 15 and 16.

Text of R and H phrases named in Pars. 2 and 3.

R10: Flammable

R37: Irritating to respiratory system

R51/53: Toxic to aquatic organisms; may cause long-term adverse effects in the aquatic environment

R65: Harmful: May cause lung damage if swallowed

R66: Repeated exposure may cause skin dryness or cracking.

R67: Vapour may cause drowsiness or dizziness

H226 Flammable liquid and vapour

H304: May be fatal through inhalation or if swallowed

H335: May cause irritation of airways

H336: May cause drowsiness or dizziness

H411: Toxic to aquatic organisms with long-term effects

EUH066: Repeated exposure may result in dry or cracked skin

Advice and training/instruction:

The product may only be used by persons instructed in the execution of the work and familiar with the

contents of this safety data sheet.

**Prepared by: Eurofins Product Testing A/S, Smedeskovvej
38, 8464 Galten, Tel.: 70 22 42 76, Fax:70 22 42 75**