

## **MULTISEAL POOL**

Multiseal POOL liquid sealant eliminates water loss in swimming pools. Multiseal Pool seals concrete and segmented basins. The seal itself does not appear in the basin.

### **Important:**

The sealing with Multiseal Pool does not protect against mechanical influences (like earth quakes) of the basin occurring after the seal is made

### **Instructions**

Circulating pump and filters have to be blocked or disconnected. The relevant amount of Multiseal Pool is then poured directly into the basin water. The mixing ratio is 1 part Multiseal Pool for 1000 Litre of pool water. If Multiseal Pool comes on tiles or other objects, it is essential immediately to wash off with plenty of water because the product will begin to crystallize and it is very difficult to remove later on - if at all.

Establish a circulation in the basin without filters. This can be done using eg a groundwater pump placed into the basin. Circulation will now have to run for 1 -3 days or until the leak in the pool is sealed. Afterwards pour the water out and rinse Basin - remnants of Multiseal Pool has to be removed mechanically. The swimming pool can now be filled again with clean water and related pool chemicals and taken into use again.

### **Disposal:**

Multiseal Pool can be discharged into sewers in highly diluted form.

### **Composition:**

Alkali, Cellulose Fibers and other additives - See MSDS.

### **Dilution:**

1.0 liters to 1000 liters of pool water.

### **Shelf Life:**

5 years from date of manufacture - Protect from frost!