

SUPER Glidex

- med silikone



PRODUCT DESCRIPTION:

SUPER GLIDEX is a snow-white, odourless silicone-based sliding agent which is applied for the assembly of O-ring sealed plastic pipes. SUPER GLIDEX has a pleasant creamy consistency. Neutral pH-value (about 7). Frost-proof.

TECHNICAL PROPERTIES:

SUPER GLIDEX simplifies installations, prevents misfitting and damaging of the rubber joint. The silicone content facilitates future adjustment or disconnection. SUPER GLIDEX prevents ageing of rubber components. SUPER GLIDEX has a very good adherence property even in wet/moist conditions and it is pleasant to work with as well as economic in use. SUPERGLIDEX may be used down to -10°C , but the product is also available in a special version which can be used down to -30°C

DIRECTIONS:

Pipes and fittings should be cleaned for sand, earth and dirt. Apply the spigot end of the pipe an even layer of SUPER GLIDEX, after which assembling can be carried out easily. SUPER GLIDEX is applied with a brush or directly on the pipe from the tube. Besides, follow assembly instructions of the pipe manufacturer. Do not ever use silicone oils in connection with painting!

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein.

CLEANING:

Clean with water. Stain in eyes should be washed away with water. NOTICE: Clean floors carefully for any spill to avoid fall accidents. Spill on the clothes is easily removed at machine-washing.

TEST:

Neither VA-approval nor other specification approvals are required for sliding agents. SUPER GLIDEX is not injurious to health when used as prescribed.

PACKAGING		Item no.	VVS-nr.	RSK-nr.	NRF-nr.	LVI-koodi
50 g. plastic tube	(24 stk./krt.)	2100005	061716000	3115116	9507843	2241403
250 g. plastic bottle	(12 stk./krt.)	2100025	061716001	3115115	9507858	2241405
400 g. plastic bottle	(12 stk./krt.)	2100040	061716002	3115121	9507871	2241408
750 g. plastic bottle	(12 stk./krt.)	2100075	061716007	3115122	9507869	2241411
1 kg. plastic tin	(6 stk./krt.)	2100100	061716008	3115123	9507872	2241412
400g SUPERGLIDEX -30°C	(12 stk./krt.)	2100041	061721004	3115125	9507874	2241418
750g SUPERGLIDEX -30°C	(12 stk./krt.)	2100751	061721008	311 51 26	950 78 75	2241421
1 kg SUPERGLIDEX -30°C	(6 stk./krt.)	2100101	061721010	311 51 27	950 78 76	2241422

Please see **SAFETY DATA SHEET**

As we constantly develop our products and we reserve the right to make changes without prior notice.