

Unigum



PRODUCT DESCRIPTION:

UNIGUM is a non-hardening, synthetic rubber compound, and does not contain solvents of any kind.

APPLICATION:

UNIGUM is primarily applied for the installation of lavatory bowls and kitchen drains plus the implant of steel kitchen sinks. However, this compound is also used for a wide range of other purposes that require a flexible, strongly adhesive rubber mastic. UNIGUM is therefore also applied for outdoor sealing of gutters, drain pipes and roofings. UNIGUM's good adherence properties also makes it suitable for such different materials as metal, wood, glass, concrete, plastic etc.

TECHNICAL PROPERTIES:

UNIGUM rubber compound

- never hardens
- remains flexible - resistant to working materials!
- remains adhesive - no future leaks!
- easy to form - also when it is cold!
- is weatherproof
- does not stick to your fingers
- can be painted
- environmentally friendly - 0% solvents of any kind
- is completely odourless

DIRECTIONS:

Generally: Clean the bearing surfaces carefully. Knead UNIGUM before using. Installation of sanitary arrangements: Fill about half up the gap between the spout and the muff with simple jointing material (possibly flax/hemp). Unroll UNIGUM in a thickness equal to the distance between spout and muff. Put UNIGUM in the gap - be careful of a smooth filling - and press well the mastic for each 1-2 cm in the height. Press towards the sides. Fill up a little over the edge of the muff and squeeze together. Cut off the surface with a knife. Implant of steel kitchen sinks: Unroll UNIGUM in a thickness of 6-8mm. Press lightly UNIGUM under the edge of the steel kitchen sink. Clamp the kitchen sink to the tabletop. Odd rubber compound which is squeezed out between kitchen sink and tabletop should be wiped away easily with a knife or a spatula. Contrary to silicone UNIGUM is non-hardening, for which reason the kitchen sink afterwards can be lifted up without any problems (in connection with service, repair or renewal) without any risk for damaging the tabletop.

Unigum

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein.

PACKAGING:		Varenr.	VVS-nr.	RSK-nr.	NRF-nr.	LVI-nr.
250 g. plastic tub	(48 pcs./box)	6500025	271555002	4050749	9507809	3265197
500 g. plastic tub	(24 pcs./box)	6500050	271555005	4050750	9507811	3265198
1,5 kg. plastic tub	(12 stk./krt.)	6500150	271555015	4050751	9507812	3265199
4,5 kg. plastic tub	-	6500450	271555045	4050752	9507813	3265200

Please see **SAFETY DATA SHEET**

As we constantly develop our products and we reserve the right to make changes without prior notice.