

Unipak



PRODUCT DESCRIPTION:

UNIPAK jointing compound is a grey, high-viscosity, paste jointing compound consisting of a saponified fatty acid, natural minerals, high grade paraffin oils and water. All the substances of the contents are permitted as additives to foodstuffs and the like.

APPLICATION:

UNIPAK jointing compound is applied together with flax/hemp, for the sealing of threaded pipe joints on potable water systems, heating systems and low pressure steam systems. (max. 140°C and 8 bar).

TECHNICAL PROPERTIES:

UNIPAK jointing compound applied together with flax/hemp provides 100% tight threaded pipe joints as well as UNIPAK facilitates connection and future disconnection of the joints. Application of UNIPAK jointing compound - contrary to e.g. thread seal tape - also provides a large adjusting flexibility as the pipe joints remain tight when loosened.

DIRECTIONS:

Flax/hemp should be applied evenly and tightly to the thread in the direction of inclination of the thread. Then the entire packed thread should be applied an adequate quantity of UNIPAK jointing compound in an even layer, after which assembling can be carried out straight away and installations be put into service. Wipe away odd jointing compound with a cloth or the like.

TESTS:

UNIPAK jointing compound's technical suitability has been repeatedly subjected to tests by the Danish Technological Institute. By this process it was proved that threaded joints properly sealed with flax/hemp and UNIPAK can remain tight up to 140°C and 8 bar. Tests also proved that UNIPAK jointing compound does not have an influence on water quality.

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein.

PACKAGING:		Item no.:	VVS-nr.	RSK-nr.	NRF-nr.	LVI-nr
65 g plastic tube	(24 pcs./box)	5000006	271351003	4051317	9507804	3265105
65 g plastic tube	(200 pcs./box)	5000007	271351003	4051317	9507804	3265105
250 g plastic tube	(48 pcs./box)	5000025	271351025	4051315	9507805	3265107
360 g plastic tube	(48 pcs./box)	5000036	271351036	4051318	9507803	3265112
4 kg tube		5000400	271351040	4051319	9507802	3265118
1 pcs. D-I-Y-set	(48 pcs./box)	5008800	271351103	-	9507807	-
1 stk. D-I-Y-set sv/fi textt	(48 stk./krt.)	5030800	-	4051175	-	3265088

Please see **SAFETY DATA SHEET**

As we constantly develop our products and we reserve the right to make changes without prior notice.