

Galvex® Cold Galvanizing

- by Unipak

Galvex® Cold Galvanizing is a galvanic action spray, anti-corrosion special paint with a very high (70-80%) content of microfine metallic zinc dust in a synthetic binder.

Galvex Cold Galvanizing spray is extremely suitable for the repair of damaged surfaces on hot-galvanized items as well as for corrosion protection of welding seams and cutting places. Also, very suitable for preliminary treatment of all surfaces where EXTRA HIGH PROTECTION against rust is required.

Glidex® Cold Galvanizing

Galvex spray, which is ready for use after a quick shaking provides a nice mat-grey colour. Galvex spray provides effective and long-acting protecting against corrosion and prevents rust from spreading from non-protected areas. Welding on Galvex protected iron is possible. Withstands constant heat effects following hardening (3-5 days) up to 110 °C - 120 °C. May be overcoated after 1-3 days. Handling dry after 5-15 min.



DIRECTIONS FOR USE:

To achieve the best possible contact between zinc particles and iron the surface has to be cleaned thoroughly for oil, dirt, loose rust and paint. An ideal preliminary treatment is sand blasting. Shake the Galvex spray before use and regular intervals while using it. Keep the spray straight-up-and-down and about 25 cm from the item. The application is done with regular motions from side to side. Release the nozzle between the motions to prevent the paint from "running". The best result is achieved by spraying "in all directions". Clean the nozzle after use by turning the spray upside down and spraying for a moment until the zinc colour no

longer appears. 2 coats of paint are recommended if only Galvex is used. Second coating can be applied after 15-20 min. Finish off with aluminum spray - if necessary - to adjust the colour to hot-galvanized items.

FOR INDUSTRIAL USE ONLY!

Contains xylene!

| Packaging | | Item no. | EAN no. | VVS no. | RSK no. | NRF no. | LVI no. |
|---------------------------|---------------|----------|---------------|-----------|---------|---------|---------|
| 500 ml. aerosol spray can | (12 pcs./box) | 2500000 | 5708923095008 | 271802005 | 4054180 | 9507785 | 3188326 |

Additional product information, safety data sheets, demo videos, instructions for use, etc. can be found at: www.unipak.dk

As we constantly develop our products, we reserve the right to be reliable.

We cannot assume responsibility for the results obtained by others over whose methods we have no control.

It is the user's responsibility to determine suitability for the user's purpose of any application methods mentioned herein.