Unigarn® Flax Sealing Yarn
- by Unipak

Unigarn® flax sealing yarn is a pure natural product made from fine, uniform, long-fibre hackled flax.

Together with sealing paste, Unigarn is suitable for sealing threaded joints. It provides tight, flexible joints and is very economical in use.
Three-strand packing yarn is used to seal glazed socket pipes or cast-iron socket pipes.
At high temperatures (>140°C), the flax fibres may scorch. If the yarn is exposed to temperatures above 130°C for extended periods, the flax fibres may scorch. However, the yarn withstands short-term exposure up to 140°C.

INSTRUCTIONS FOR USE:

Apply Unigarn evenly and tightly along the full length of the thread in the direction of assembly. Then apply sealing paste evenly over the wrapped thread. Tighten the joint immediately; the system is then ready for use.

Packaging	Carton	Item no.	EAN no.	VVS no.	RSK no.	NRF no.	LVI no.
40 g spool in dispenser	(50 kg/bag)	1500410	5708923096111	271302004	4054139	9507866	3265074
80 g spool	(10/250 pcs./ctn.)	1500850	5708923096005	271302008	4054111	9507851	3265042
80 g spool in dispenser	(1/192 pcs./ctn.)	1500820	5708923096203	271302508	4054138	9507899	3265071
100 g hank	(8/80 pcs./ctn.)	1500950	5708923096906	271303010	4054112	9507853	3265072
100 g bundle	(50 kg/bag)	1500010	5708923150264	271301510	4054129	9507854	3265036

10/2026

Further product information, safety data sheets, demonstration videos and instructions are available at: www.unipak.dk
We continuously develop our products and reserve the right to make changes without prior notice.
The above information is based on tests and experience. As the product's use is beyond our control, a trial installation is recommended to ensure suitability for the intended application.

Unipak®
Unipak A/S | Marktoften 3C
8464 Galten | Denmark
www.Unipak.dk