

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

UNIPAK Rust Penetrant

Product no.

-

REACH registration number

Not applicable

Other means of identification

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

rust-dissolver and corrosion protection

Uses advised against

-

The full text of any mentioned and identified use categories are given in section 16

1.3. Details of the supplier of the safety data sheet

Company and address

Unipak A/S
Marktoften 3C
8464 Galten
Denmark

E-mail

Salesunipak.dk

SDS date

22-04-2015

SDS Version

1.0

1.4. Emergency telephone number

+45 8626 1177 (normal opening time)

These services are only available to health professionals.

The UK National Poisons Emergency number is 0870 600 6266

Use your national or local emergency number

See section 4 "First aid measures"

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol 1, // H229, H222

See full text of H/R-phrases in section 2.2.

DPD/DSD Classification

F+; R12

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger!

Hazard statement(s)

Extremely flammable aerosol. (H222)
 Pressurised container: May burst if heated. (H229)

Safety statement(s)	General	-
	Prevention	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210) Do not spray on an open flame or other ignition source. (P211) Do not pierce or burn, even after use. (P251)
	Response	-
	Storage	Store in a well-ventilated place. (P403) Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. (P410+P412)
	Disposal	-

Identity of the substances primarily responsible for the major health hazards

-

2.3. Other hazards

Additional labelling

-

Additional warnings

-

VOC

-

SECTION 3: Composition/information on ingredients

3.1/3.2. Substances

NAME: solventnaphtha (råolie), let aromatisk, <0,1%benzene
 IDENTIFICATION NOS.: CAS-no: 64742-95-6 EC-no: 265-199-0 Index-no: 649-356-00-4
 CONTENT: 40-60%
 DSD CLASSIFICATION: Xn;R65
 CLP CLASSIFICATION: Asp. Tox. 1
 H304

NAME: Butane
 IDENTIFICATION NOS.: CAS-no: 106-97-8 EC-no: 203-448-7 Index-no: 601-004-00-0
 CONTENT: <20%
 DSD CLASSIFICATION: F+; R12
 CLP CLASSIFICATION: Flam. Gas 1
 H220

NAME: isobutane
 IDENTIFICATION NOS.: CAS-no: 75-28-5 EC-no: 200-857-2 Index-no: 601-004-00-0
 CONTENT: <20%
 DSD CLASSIFICATION: F+; R12
 CLP CLASSIFICATION: Flam. Gas 1
 H220

NAME: propane
 IDENTIFICATION NOS.: CAS-no: 74-98-6 EC-no: 200-827-9 Index-no: 601-003-00-5
 CONTENT: <20%
 DSD CLASSIFICATION: F+; R12
 CLP CLASSIFICATION: Flam. Gas 1
 H220

(*) See full text of H/R-phrases in chapter 16. Occupational exposure limits are listed in section 8, if these are available.

Other informations

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor, if in doubt about the injured person's condition or if the symptoms continue. Never give an unconscious person water or similar.

Inhalation

Get the injured person into fresh air. Make sure there is always someone with the injured person. Prevent shock by keeping the injured person warm and calm. If the person stops breathing, give mouth-to-mouth resuscitation. If unconscious, roll the injured person onto side with the top leg bent at both knee and hip. Call an ambulance.

Skin contact

Remove contaminated clothing and shoes at once. Skin that has come in contact with the material must be washed thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Remove contact lenses. Flush eyes immediately with plenty of water (20-30°C) for at least 15 minutes and continue until irritation stops. Make sure you flush under the upper and lower eyelids. If irritation continues, contact a doctor.

Ingestion

Give the person plenty to drink and stay with the person. If the person feels unwell, contact a doctor immediately and take this safety data sheet or the label from the product with you. Do not induce vomiting unless recommended by the doctor. Hold head facing down so that no vomit runs back into the mouth and throat.

Burns

Rinse with water until the pain stops and continue for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

No special

4.3. Indication of any immediate medical attention and special treatment needed

No special

Information to medics

Bring this safety data sheet.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended: alcohol-resistant foam, carbonic acid, powder, water mist. Water jets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

If the product is exposed to high temperatures, as in the case of fire, dangerous catabolic substances are produced. These are: Carbon oxides. Fire will result in thick black smoke. Exposure to catabolic products can damage your health. Fire fighters should use proper protection gear. Closed containers, which are exposed to fire, should be cooled with water. Do not let fire-extinguishing water run into sewers and other water courses.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours from waste material. Stores that have not ignited must be cooled by water mist. Where possible, remove flammable materials. Make sure there is sufficient ventilation.

6.2. Environmental precautions

No specific requirements.

6.3. Methods and material for containment and cleaning up

According to EC-Regulation 1907/2006 (REACH)

Use sand, sawdust, earth, vermiculite, diatomaceous earth to contain and collect non-combustible absorbent materials and place in container for disposal, according to local regulations. Cleaning should be done as far as possible using normal cleaning agents. Solvents should be avoided.

6.4. Reference to other sections

See section on "Disposal considerations" with regard to the handling of waste. See section on 'Exposure controls/personal protection' for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Smoking, consumption of food or liquid, and storage of tobacco, food or liquids are not allowed in the workrooms. See section on 'Exposure controls/personal protection' for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Always store in containers of the same material as the original. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Must be stored in a cool and ventilated area, away from possible sources of combustion.

Storage temperature

10 – 45°C

7.3. Specific end use(s)

This product should only be used for applications described in Section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

OEL

Butane and isobutane (EH40, 2005)

Long-term exposure limit (8-hour TWA reference period): 600 ppm | 1450 mg/m³

Short-term exposure limit (15-minute reference period): 750 ppm | 1810 mg/m³

Comments: Carc (>0,1%butadien) (Carc = Capable of causing cancer.)

DNEL / PNEC

No data available.

8.2. Exposure controls

Compliance with the stated exposure limits values should be checked on a regular basis.

General recommendations

▼ Observe general occupational hygiene.

Exposure scenarios

If there is an appendix to this safety data sheet, the indicated exposure scenarios must be complied.

Exposure limits

Trade users are covered by the rules of the working environment legislation on maximum concentrations for exposure. See work hygiene threshold values below.

Appropriate technical measures

Airborne gas and dust concentrations must be kept as low as possible and below the current threshold values (see below). Use for example an exhaust system if the normal air flow in the work room is not sufficient. Make sure that eyewash and emergency showers are clearly marked.

Hygiene measures

Whenever you take a break in using this product and when you have finished using it, all exposed areas of the body must be washed. Always wash hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment



Generally

Only CE-marked personal protection equipment should be used. Use only CE marked protective equipment.

According to EC-Regulation 1907/2006 (REACH)

Respiratory Equipment

Recommended: A.

Skin protection

Special work clothing should be used. When working with this product for a long period of time, use a protective suit.

Hand protection

Recommended: Nitrile rubber.

Eye protection

Use face shield. Use safety glasses with a side shield as an alternative.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form	Colour	Odour	pH	Viscosity	Density (g/cm ³)
Aerosol	Clear	Solvent	-	-	-

Phase changes

Melting point (°C)	Boiling point (°C)	Vapour pressure (mm Hg)
-	-	-

Data on fire and explosion hazards

Flashpoint (°C)	Ignition (°C)	Self ignition (°C)
-	-	-

Explosion limits (Vol %)	Oxidizing properties
-	-

Solubility

Solubility in water	n-octanol/water coefficient
Insoluble	-

9.2. Other information

Solubility in fat	Additional information
-	N/A

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in the section on "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reductants agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Substance	Species	Test	Route of exposure	Result
butane	Rat	LC50	Inhalation	1237 mg/L 2h
solventnaphtha (råolie), let a...	Rat	LD50	Oral	> 5000 mg/kg bw
solventnaphtha (råolie), let a...	Rabbit	LD50	Dermal	> 2000 mg/kg bw
solventnaphtha (råolie), let a...	Rat	LC50	Inhalation	> 5610 mg/m ³ air 4h

Skin corrosion/irritation

No data available.

Serious eye damage/irritation

No data available.

Respiratory or skin sensitisation

No data available.

According to EC-Regulation 1907/2006 (REACH)

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Long term effects

No special

SECTION 12: Ecological information

12.1. Toxicity

Substance	Species	Test	Test duration	Result
butane	Daphnia	LC50	48h	14,22 mg/L
butane	Fish	LC50	96h	27,98 mg/L
butane	Algae	EC50	96h	7,71 mg/L
solventnaphtha (råolie), let a...	Fish	LC50	48h	5,4 mg/L
solventnaphtha (råolie), let a...	Algae	EC50	96h	64 mg/L

12.2. Persistence and degradability

Substance	Biodegradability	Test	Result
No data available.			

12.3. Bioaccumulative potential

Substance	Potential bioaccumulation	LogPow	BFC
No data available.			

12.4. Mobility in soil

butane : Log Koc= 0,941571, Calculated from LogPow (High mobility potential.).

12.5. Results of PBT and vPvB assessment

No data available

12.6. Other adverse effects

No special

SECTION 13: Disposal considerations

13.1. Waste treatment methods

The product is covered by the regulations on dangerous waste.

Waste

EWC code
16 05 04

Specific labelling

-

Contaminated packing

Packaging which contains leftovers from the product must be disposed of in the same way as the product.

SECTION 14: Transport information

This product is covered by the conventions on dangerous goods.

14.1 – 14.4

ADR/RID

14.1. UN number	1950
14.2. UN proper shipping name	AEROSOLS
14.3. Transport hazard class(es)	2.1
14.4. Packing group	-
Notes	-
Tunnel restriction code	-

According to EC-Regulation 1907/2006 (REACH)

IMDG

UN-no.	1950
Proper Shipping Name	AEROSOLS
Class	-
PG*	-
EmS	F-D, S-U
MP**	-
Hazardous constituent	-

IATA/ICAO

UN-no.	
Proper Shipping Name	
Class	
PG*	

14.5. Environmental hazards

-

14.6. Special precautions for user

-

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

No data available

(*) Packing group

(**) Marine pollutant

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

-

Demands for specific education

-

Additional information

-

Sources

EC regulation 1907/2006 (REACH)

Directive 2000/532/EC

EC Regulation 1272/2008 (CLP)

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H/R-phrases as mentioned in section 3

R12 - Extremely flammable.

R65 - Harmful: may cause lung damage if swallowed.

H220 - Extremely flammable gas.

H304 - May be fatal if swallowed and enters airways.

The full text of identified uses as mentioned in section 1

-

Other symbols mentioned in section 2



Other

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

According to EC-Regulation 1907/2006 (REACH)

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

A change (in proportion to the last essential change (first cipher in SDS version)) is marked with a blue triangle.

The safety data sheet is validated by

**Date of last essential change
(First cipher in SDS version)**

-

**Date of last minor change
(Last cipher in SDS version)**

-

ALPHAOMEGA. Licens nr.:3015391111, Unipak A/S
www.chymeia.com