

Unipak[®] Geotextile - elastic non-woven cloth for waterproofing and airtight construction, for use in combination with HBS-200[®]

Unipak Geotextile is suitable for use in combination with HBS-200[®] Liquid Rubber in case of seam, crack and tear-bridging applications.

Suitable for sealing and protecting a wide variety of materials, such as concrete, metal, stone, wood, bitumen, zinc, PVC, EPDM (test first), etc. For floors, partitions, walls, seams, joints, conduits and structural components.

Excellent for both interior and exterior applications (bathrooms, cellars, balconies, roofs, etc.) including gutters, shower basins, conduit ducts, floor seams, expansion joints, window frame joints and ground level items. Also suitable as a waterproof layer under tiles in damp environments, such as bathrooms, swimming pools, balconies, terraces, etc.



DIRECTIONS FOR USE

Before using HBS-200[®] Liquid Rubber, stir manually until a homogenous colour is obtained.

It is not recommended to use an electric mixer with a high rotational speed for stirring. For seam, crack and tear-bridging applications, Unipak Geotextile should be used.

1. Unipak Geotextile must be applied in still wet HBS-200[®] Liquid Rubber.
2. Then immediately level off with a second layer. Always ensure a layer thickness of at least 2 mm after curing.

PROPERTIES

- Elastic
- Excellent absorption of HBS-200[®]
- Strong
- Non-woven

Emballage	Carton	Item no.	EAN no.	VVS no.	RSK no.	NRF no.	LVI no.
Roll	3	7006958	8710439313665	251252230	2006007	1429444	3265059

Additional product information, safety data sheets, demo videos, instructions for use, etc. can be found at: www.unipak.dk

As we constantly develop our products, we reserve the right to be reliable.

We cannot assume responsibility for the results obtained by others over whose methods we have no control.

It is the user's responsibility to determine suitability for the user's purpose of any application methods mentioned herein.