

Glidex[®] Tap Lubricant

- by Unipak

Glidex[®] Tap Lubricant is approved for drinking water.

Glidex[®] Tap Lubricant is produced from 100% pure odorless, silicone oil. Glidex Tap Lubricant is available in a small 30g handy plastic tube and in 900g plastic tub.

Glidex[®] Tap Lubricant

Glidex[®] Tap Lubricant is manufactured for lubrication of O-rings in drinking water faucets. Glidex Tap Lubricant is particularly well suited to EPDM and NBR rubber. Temperature ranges from -40° to +200°C. Meets the German TZW/UBA requirements for use in drinking water installations.

Approved for drinking water GDV 06/00005



DIRECTIONS FOR USE:

1. Clean all parts for lime, dirt, sand etc.
2. Apply a suitable amount of Glidex Tap Lubricant and assemble the tap, according to the manufacturer's directions.

CAUTION! Spills on floors and shoe soles may cause high risk of fall accidents.

Never use silicone oils in connection with painting jobs. Even small amounts may cause adhesion problems.

Emballage		Item no.	EAN no.	VVS no.	RSK no.	NRF no.	LVI no.
30 g. tube	(24 pcs./box)	2010003	5708923210036	745314030	8346010	9507799	3265410
900 g. can	(6 pcs./box)	2010090	5708923210906	745314090	8346012	9507801	3265411
D-I-Y kit 30 g. tube		2010803	5708923201034	745314230	8346011	9507895	2241401

Additional product information, safety data sheets, demo videos, instructions for use, etc. can be found at: www.unipak.dk

As we constantly develop our products, we reserve the right to be reliable.

We cannot assume responsibility for the results obtained by others over whose methods we have no control.

It is the user's responsibility to determine suitability for the user's purpose of any application methods mentioned herein.