

Sprinkler Lubricant Glidex®

- by Unipak

Sprinkler Lubricant Glidex® ensures easy and problem-free installation, prevents drying and aging of rubber joints.

Sprinkler Lubricant Glidex®

Sprinkler Lubricant Glidex® has a temperature range from -50 °C to +200 °C, and an excellent adhesion even under wet/damp conditions.



DIRECTIONS:

1. Clean pipes and fittings
2. Apply an even and thin layer of Sprinkler Glidex® to sprinkler joint. After this assembling can be carried out easily.
3. Clean with water and soap

Never use silicone bases products during painting operations as even small amounts of silicone may cause failing paision.

CLEANING:

Clothes: Stains/spills are easily removed by machine-washing
Skin contact: Rinse with soap and water
Eye contact: Rinse with water

NOTICE! Clean floors carefully for any spills to avoid slip accidents.

Packaging		Item no.	EAN no.	VVS no.	RSK no.	NRF no.	LVI no.
1 kg. plastic tub	(6 pcs./box)	2270100	5708923905291	061719008	3136141	9507782	3267668

Additional product information, safety data sheets, demo videos, instructions for use, etc. can be found at: www.unipak.dk

As we constantly develop our products, we reserve the right to be reliable.

We cannot assume responsibility for the results obtained by others over whose methods we have no control.

It is the user's responsibility to determine suitability for the user's purpose of any application methods mentioned herein.