

SPRINKLER

Glidex



PRODUCT DESCRIPTION:

Silicone based assembly paste for sprinkler pipes.

Non-drip, anti-corrosive and freezeproof.

TECHNICAL PROPERTIES:

- Simplifies installation, prevents misfitting and damage to rubber joints.
- Prevents drying out and ageing of rubbers.
- Temperature range: from -50 to +200°C.
- Excellent adhesion even under wet/damp conditions.

DIRECTIONS:

- Clean pipes and fittings.
- Apply an even and thin layer of SPRINKLER GLIDEX to sprinkler joint. After this assembling can be carried out easily.
- Follow assembly instructions of the pipe manufacturer.
- Clean with water and soap.
- NOTICE: Clean floors carefully for any spills to avoid slip accidents. Never use silicone based products during painting operations as even small amounts of silicone may cause failing paint adhesion.

CLEANING:

- Clothes: Stains/spills are easily removed by machine-washing.
- Skin contact: Rinse with soap and water.
- Eye contact: Rinse with water.

PACKAGING							
		Item no.	EAN-no.	VVS-nr.	RSK-nr.	NRF-nr.	LVI-koodi
1 kg plastic tub	(6 pcs/box)	2270100	5708923905291	061719008	3136141	9507782	3267668

Please also see **SAFETY DATA SHEET**.

As we constantly develop our products we reserve the right to make changes without prior notice. The data contained in this datasheet are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any application methods mentioned herein.