

Glidex Spray 20%

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Glidex Spray 20%

Product no.

2000000, 2050000

Unique formula identifier (UFI)

6000-E083-C00R-U52T

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Lubricant

Uses advised against

No special

1.3. Details of the supplier of the safety data sheet

Company and address

Unipak A/S

Marktoften 3C

8464 Galten

Denmark

+45 8626 1177

www.unipak.dk

E-mail

sales@unipak.dk

Revision

24/03/2022

SDS Version

1.0

1.4. Emergency telephone number

Contact The National Poisons Information Service (dial 111, 24 h service).

See section 4 "First aid measures".

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)

Safety statement(s)

General

Keep out of reach of children. (P102)

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

If medical advice is needed, have product container or label at hand. (P101)

Read label before use. (P103)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Do not pierce or burn, even after use. (P251)

Do not spray on an open flame or other ignition source. (P211)

Response

-

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal

-

Hazardous substances

No special

2.3. Other hazards

Additional labelling

Not applicable

Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
butane	CAS No.: 106-97-8 EC No.: 203-448-7 REACH: 01-2119474691-32 Index No.: 601-004-01-8	50-<75%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	
propane	CAS No.: 74-98-6 EC No.: 200-827-9 REACH: 01-2119486944-21 Index No.: 601-003-00-5	10-<25%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	
isobutane	CAS No.: 75-28-5 EC No.: 200-857-2 REACH: 01-2119485395-27 Index No.: 601-004-01-8	1-<5%	Flam. Gas 1A, H220 Press. Gas (Liq.) , H280	

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

No special

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet. Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes immediately. Ensure to wash exposed skin thoroughly with water and soap. Skin cleanser can be used. DO NOT use solvents or thinners.

Eye contact

Upon irritation of the eye: Remove contact lenses. Flush eyes with plenty of water or salt water (20-30°C) and continue until irritation stops. Normally rinsing for less than 5 minutes is sufficient.

Ingestion

Provide plenty of water for the person to drink and stay with him/her. In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the victim lean forward with head down to avoid inhalation of- or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

No special

4.3. Indication of any immediate medical attention and special treatment needed

No special

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂).

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

6.3. Methods and material for containment and cleaning up

Minor spills are collected with a cloth. Shall be contained in suitable and tightly closed disposal containers.

6.4. Reference to other sections

See section 13 on "Disposal considerations" in regard of handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Because of the danger of self-ignition, any waste from the product, spray mist and soiled rags etc. are to be kept in a fire-proof place in air-tight containers, alternatively the waste is to be burned.

Smoking, drinking and consumption of food is not allowed in the work area.

See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material

Always store in containers of the same material as the original container.

Storage temperature

5 - 45°C

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

—
butane

Long term exposure limit (8 hours) (ppm): 600

Long term exposure limit (8 hours) (mg/m³): 1450

Short term exposure limit (15 minutes) (ppm): 750

Short term exposure limit (15 minutes) (mg/m³): 1810

Annotations:

Carc1 = Capable of causing cancer and/or heritable genetic damage if it contains more than 0.1% of buta-1,3-diene.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002. EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

No data available

PNEC

No data available

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See

occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Always wash hands, forearms and face.

Measures to avoid environmental exposure


No specific requirements

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.


Respiratory Equipment

Work situation	Type	Class	Colour	Standards	
In case of inadequate ventilation	A	Class 2 (medium capacity)	Brown	EN14387	


Skin protection

Recommended	Type/Category	Standards
No special when used as intended	-	-

Hand protection

Work situation	Material	Glove thickness (mm)	Breakthrough time (min.)	Standards	
In the likelihood of direct or incidental exposure.	Nitrile	0,3	120	EN374-2	

Eye protection

Type	Standards	
In the likelihood of direct or incidental exposure, use face protection.	EN166	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Form

Aerosol

Colour

Various colours

Odour

Characteristic

Odour threshold (ppm)

Testing not relevant or not possible due to nature of the product.

pH

Testing not relevant or not possible due to nature of the product.

Density (g/cm³)

Testing not relevant or not possible due to nature of the product.

Viscosity

Testing not relevant or not possible due to nature of the product.

Phase changes

Melting point (°C)

Testing not relevant or not possible due to nature of the product.

Boiling point (°C)

-161.5

Vapour pressure

Testing not relevant or not possible due to nature of the product.

Vapour density

Testing not relevant or not possible due to nature of the product.

Decomposition temperature (°C)

Testing not relevant or not possible due to nature of the product.

Evaporation rate (n-butylacetate = 100)

Data on fire and explosion hazards

Flash point (°C)

Does not apply to aerosols.

Ignition (°C)

Testing not relevant or not possible due to nature of the product.

Auto flammability (°C)

287

Explosion limits (% v/v)

5 - 15

Explosive properties

Testing not relevant or not possible due to nature of the product.

Oxidizing properties

Testing not relevant or not possible due to nature of the product.

Solubility

Solubility in water

Testing not relevant or not possible due to nature of the product.

n-octanol/water coefficient

Testing not relevant or not possible due to nature of the product.

Solubility in fat (g/L)

Testing not relevant or not possible due to nature of the product.

9.2. Other information

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

No special

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

The product is not degraded when used as specified in section 1.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Acute toxicity

Product/substance	butane
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	1237 mg/l 2h. ·
Other information	

Product/substance	propane
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	1237 mg/l air 2h. ·
Other information	

Product/substance	isobutane
Test method	
Species	Rat
Route of exposure	Inhalation
Test	LC50
Result	1237 mg/l 2h. ·
Other information	

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Long term effects

No special

Other information

No special

SECTION 12: Ecological information

12.1. Toxicity

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Product/substance	butane
Test method	
Species	Algae
Compartment	
Duration	96 hours
Test	EC50
Result	7,71 mg/L ·
Other information	

Product/substance	propane
Test method	
Species	Fish
Compartment	
Duration	96 hours
Test	LC50
Result	27,98 mg/l ·
Other information	

Product/substance	propane
Test method	
Species	Algae
Compartment	
Duration	96 hours
Test	EC50
Result	7,71 mg/l ·
Other information	

Product/substance	propane
Test method	
Species	Daphnia
Compartment	
Duration	48 hours
Test	LC50
Result	46,6 mg/l ·
Other information	

Product/substance	isobutane
Test method	
Species	Fish
Compartment	
Duration	96 hours
Test	LC50
Result	49,9 mg/l ·
Other information	

Product/substance	isobutane
Test method	
Species	Algae
Compartment	
Duration	96 hours
Test	EC50

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

Result 19,37 mg/l ·
Other information

12.2. Persistence and degradability

No data available

12.3. Bioaccumulative potential

Product/substance	butane
Test method	
Potential bioaccumulation	Yes
LogPow	1.0900
BCF	No data available
Other information	

Product/substance	propane
Test method	
Potential bioaccumulation	Yes
LogPow	1,0900
BCF	No data available
Other information	

Product/substance	isobutane
Test method	
Potential bioaccumulation	Yes
LogPow	1,0900
BCF	No data available
Other information	

12.4. Mobility in soil

butane

LogKoc = 0.941571, High mobility potential.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances considered to meet the criteria classifying them as PBT and/or vPvB.

12.6. Other adverse effects

This product contains substances with the potential of bioaccumulation resulting in the risk of accumulation in the food chain. Bioaccumulative substances are concentrated in adipose tissue and are not easily secreted.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product is covered by the regulations on hazardous waste.

HP 3 - Flammable

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

EWC code

16 05 04* Gases in pressure containers (including halons) containing dangerous substances




Specific labelling

Not applicable

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information
ADR	UN1950	AEROSOLS	Class: 2 Labels: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information.
IMDG	UN1950	AEROSOLS	Class: 2 Labels: 2.1 Classification code: 5F 	-	No	Limited quantities: 1 L EmS: F-D S-U See below for additional information.
IATA	UN1950	AEROSOLS	Class: 2 Labels: 2.1 Classification code: 5F 	-	No	See below for additional information.

* Packing group

** Environmental hazards

Additional information

IMDG / See the Dangerous Goods List, section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

This product is within scope of the regulations of transport of dangerous goods.

14.6. Special precautions for user

Not applicable

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Demands for specific education

No specific requirements

SEVESO - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

Additional information

Not applicable

Sources

The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29)

Control of Major Accident Hazards (COMAH) Regulations 2015.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste.

CLP Regulation (EC) No 1272/2008, as retained and amended in UK law.

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

EC-Regulation 1907/2006 (REACH), as amended by UK REACH Regulations SI 2019/758

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H220, Extremely flammable gas.

H280, Contains gas under pressure; may explode if heated.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit.

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVCB = Complex hydrocarbon substance

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of physical hazards has been based on experimental data.

The safety data sheet is validated by

tn

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a blue triangle.

According to EC-Regulation 1907/2006 (REACH), annex II, as implemented by EC-Regulation 2015/830

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en