

SAFETY DATA SHEET

PE CLEANER WIPES SPECIAL

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

PE CLEANER WIPES SPECIAL

Other names / Synonyms

Unipak PE CLEANER WIPES SPECIAL

Product no.

7005745, 7005760

Other means of identification

Index No.: 603-002-00-5

EC No.: 200-578-6

CAS No.: 64-17-5

Unique formula identifier (UFI)

XU73-PAX6-UM76-KNC1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Cleaning product

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

Company and address

Unipak A/S

Marktoften 3C

8464 Galten

Denmark

+45 8626 1177

www.unipak.dk

E-mail

sales@unipak.dk

Revision

21/05/2025

SDS Version

1.0

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 112 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Flam. Sol. 1; H228, Flammable solid.

Eye Irrit. 2; H319, Causes serious eye irritation.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Flammable solid. (H228)

Causes serious eye irritation. (H319)

Precautionary statement(s)

General

If medical advice is needed, have product container or label at hand. (P101)

Keep out of reach of children. (P102)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)

Keep container tightly closed. (P233)

Response

-

Storage

-

Disposal

Dispose of contents/container in accordance with local regulation (P501)

Hazardous substances

Does not contain any substances required to report

Additional labelling

UFI: XU73-PAX6-UM76-KNC1

2.3. Other hazards

Additional warnings

Dust from flammable solids can be explosive, even if they are not hazardous substances.

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Product/substance	Identifiers	% w/w	Classification	Note
ethanol;ethyl alcohol	CAS No.: 64-17-5 EC No.: 200-578-6 UK-REACH: Index No.: 603-002-00-5	60-80%	Flam. Liq. 2, H225 Eye Irrit. 2, H319 (SCL: 50.00 %)	

Constituents

Product/substance	Identifiers	% w/w	Classification	Note
methanol	CAS No.: 67-56-1 EC No.: 200-659-6 UK-REACH: Index No.:	<1%	Flam. Liq. 2, H225 Acute Tox. 3, H301 Acute Tox. 3, H311 Acute Tox. 3, H331 STOT SE 1, H370 STOT SE 2, H371 (SCL: 3.00 %)	[1], [3]

3.2. Mixtures

Not applicable. This product is a substance.

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No specific requirements

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

If the product is exposed to high temperatures, e.g. in the event of fire, dangerous decomposition compounds are produced. These are:

Carbon oxides (CO / CO₂)

5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: 1Z

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure sufficient ventilation.

Ensure adequate ventilation, especially in confined areas.

Contaminated areas may be slippery.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc.

Keep unauthorized persons away from the spill

6.3. Methods and material for containment and cleaning up

Clean up manually and place in appropriate containers for disposal.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.

See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Ensure sufficient ventilation. Fumes are heavier than air and may accumulate near the floor or in confined spaces.

Smoking, drinking and consumption of food is not allowed in the work area.

7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

According to national regulation.

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

ethanol;ethyl alcohol

Long term exposure limit (8 hours) (ppm): 1000

Long term exposure limit (8 hours) (mg/m³): 1920

methanol

Long term exposure limit (8 hours) (ppm): 200

Long term exposure limit (8 hours) (mg/m³): 266

Short term exposure limit (15 minutes) (ppm): 250

Short term exposure limit (15 minutes) (mg/m³): 333

Annotations:

Sk = Can be absorbed through the skin and lead to systemic toxicity.

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

DNEL

ethanol;ethyl alcohol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	206 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	343 mg/kg bw/day

Long term – Systemic effects - General population	Inhalation	114 mg/m ³
Long term – Systemic effects - Workers	Inhalation	380 mg/m ³
Short term – Local effects - General population	Inhalation	950 mg/m ³
Short term – Local effects - Workers	Inhalation	1900 mg/m ³
Long term – Systemic effects - General population	Oral	87 mg/kg bw/day

methanol

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	4 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	20 mg/kg bw/day
Short term – Systemic effects - General population	Dermal	4 mg/kg bw/day
Short term – Systemic effects - Workers	Dermal	20 mg/kg bw/day
Long term – Local effects - General population	Inhalation	26 mg/m ³
Long term – Local effects - Workers	Inhalation	130 mg/m ³
Long term – Systemic effects - General population	Inhalation	26 mg/m ³
Long term – Systemic effects - Workers	Inhalation	130 mg/m ³
Short term – Local effects - General population	Inhalation	26 mg/m ³
Short term – Local effects - Workers	Inhalation	130 mg/m ³
Short term – Systemic effects - General population	Inhalation	26 mg/m ³
Short term – Systemic effects - Workers	Inhalation	130 mg/m ³
Long term – Systemic effects - General population	Oral	4 mg/kg bw/day
Short term – Systemic effects - General population	Oral	4 mg/kg bw/day

PNEC

ethanol;ethyl alcohol

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		960 µg/L
Freshwater sediment		3.6 mg/kg
Intermittent release (freshwater)		2.75 mg/L
Marine water		790 µg/L
Marine water sediment		2.9 mg/kg
Sewage treatment plant		580 mg/L
Soil		630 µg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

The formation of vapours must be kept at a minimum and below current limit values (see above). Installation of a local exhaust system if normal air flow in the work room is not sufficient is recommended. Ensure eyewash and emergency showers are clearly marked.

Hygiene measures

In between use of the product and at the end of the working day all exposed areas of the body must be washed thoroughly. Pay special attention to hands, forearms and face.

Measures to avoid environmental exposure

No specific requirements.

Individual protection measures, such as personal protective equipment

Generally

Use only CE marked protective equipment.

Respiratory Equipment

No specific requirements

Skin protection

Recommended	Type/Category	Standards
No special when used as intended.	-	-

Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	> 0.12	≥ 10	EN374-3, Level 1



Eye protection

Work situation	Type	Standards
When there is risk of splash- / intermittent exposure	Safety glasses with side shields.	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Solid

Colour

Clear

Odour / Odour threshold

Alcohol odor

pH

No data available.

Density (g/cm³)

0.785 (20 °C)

Kinematic viscosity

1.5 mm²/s (20 °C)

Dynamic viscosity

1,2 mPa.s (20 °C)

Particle characteristics

No data available.

Phase changes

Melting point/Freezing point (°C)

-89,5

Softening point/range (°C)

Does not apply to solids.

Boiling point (°C)

78

Vapour pressure

280 hPa (50 °C)

Relative vapour density

Does not apply to solids.

Decomposition temperature (°C)

No data available.

Data on fire and explosion hazards

Flash point (°C)

13

Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

425

Lower and upper explosion limit (% v/v)

3.5 - 15

Solubility

Solubility in water

No data available.

n-octanol/water coefficient (LogKow)

No data available.

Solubility in fat (g/L)

No data available.

9.2. Other information

Oxidizing properties

No data available.

Other physical and chemical parameters

VOC: 63,8 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

Acute toxicity

Product/substance	ethanol;ethyl alcohol
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	10470 mg/kg

Product/substance	ethanol;ethyl alcohol
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	>2000 mg/kg

Product/substance	ethanol;ethyl alcohol
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50 (4 hours)
Result:	120 mg/L

Product/substance	methanol
-------------------	----------

Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	10470 mg/kg

Product/substance	methanol
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	300 mg/kg

Based on available data, the classification criteria are not met.

Skin corrosion/irritation

Based on available data, the classification criteria are not met.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Based on available data, the classification criteria are not met.

Reproductive toxicity

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs.

Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

None known.

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

None known.

SECTION 13: Disposal considerations

Waste treatment methods

Product is covered by the regulations on hazardous waste. (*)

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

20 01 13* Solvents

Specific labelling

Contaminated packing

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatio n:
ADR	UN1325	FLAMMABLE SOLID, ORGANIC, N.O.S. (ethanol;ethyl alcohol)	Transport hazard class: 4.1 Label: 4.1 Classification code: F1 	II	No	Limited quantities: 1 kg Tunnel restriction code: (E) See below for additional information .
IMDG	UN1325	FLAMMABLE SOLID, ORGANIC, N.O.S. (ethanol;ethyl alcohol)	Transport hazard class: 4.1 Label: 4.1 Classification code: F1 	II	No	Limited quantities: 1 kg EmS: F-A S-G See below for additional information .
IATA	UN1325	FLAMMABLE SOLID, ORGANIC, N.O.S. (ethanol;ethyl alcohol)	Transport hazard class: 4.1 Label: 4.1 Classification code: F1 	II	No	See below for additional information .

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

Hazchem Code: 1Z

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

No special.

Demands for specific education

No specific requirements.

Control of Major Accident Hazards (COMAH) - Categories / dangerous substances

Not applicable.

UK-REACH, Annex XVII

ethanol;ethyl alcohol is subject to UK-REACH restrictions (entry 40).

Additional information

Tactile warning.

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

Full text of H-phrases as mentioned in section 3

H225, Highly flammable liquid and vapour.

H319, Causes serious eye irritation.

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System
EWC = European Waste Catalogue
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
GWP = Global warming potential
IARC = International Agency for Research on Cancer (IARC)
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)
OECD = Organisation for Economic Co-operation and Development
PBT = Persistent, Bioaccumulative and Toxic
PNEC = Predicted No Effect Concentration
RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail
RRN = REACH Registration Number
SCL = A specific concentration limit
SVHC = Substances of Very High Concern
STOT-RE = Specific Target Organ Toxicity - Repeated Exposure
STOT-SE = Specific Target Organ Toxicity - Single Exposure
TWA = Time weighted average
UN = United Nations
UVBC = Unknown or variable composition, complex reaction products or of biological materials
VOC = Volatile Organic Compound
vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

The safety data sheet is validated by

THA

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en