Unipak® Chamfering tool

- by Unipak

Unipak® Chamfering tool

For chamfering plastic pipes of PVC, PVC-C, ABS, PP and PE.
Suitable for diameters 16 ≤ 63 mm.

DIRECTIONS FOR USE

PREPARATION

Surface Requirements: Synthetic pipes need to be clean, dry and free of grease.

DIRECTIONS FOR USE

Five adapter rings for diameter 20, 25, 32, 40 and 50 mm are integrated into the chamfering tool.

To place these:

1. Loosen the screws.
2. Place the adapter rings of the desired diameter (for example, for a diameter of 40 mm place the adapter ring with a diameter of 50 and 40).
3. Tighten the screw (not further than the adapter rings).
4. The other adapter rings can be placed on the rear of the chamfering tool. Place the chamfering tool over the pipe and move it around until the entire pipe has a rim of 15°.

Points of attention: Do not apply pressure on the pipe.

STORAGE CONDITIONS

Our advice is based on extensive research and practical experience.

PROPERTIES

- Creates a chamfered edge of 15°
- Prevents adhesive 'crowding out'

Packaging	Carton	Item no.	VVS no.	RSK no.	NRF no.	LVI no.
Bag	6	7009080	234076063	3870230	1490723	7012458

02/2026

Additional product information, safety data sheets, demo videos, instructions for use, etc. can be found at: www.unipak.dk
As we constantly develop our products, we reserve the right to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any application methods mentioned herein.